

NASA TECHNICAL  
MEMORANDUM

NASA TM X-64534

INTERPOLATION OF BODE'S TABLES OF THE  
SOLAR CONTINUOUS ABSORPTION COEFFICIENT

By Edward M. Wadsworth  
Space Sciences Laboratory

July 1, 1970

CASE FILE  
COPY

NASA

*George C. Marshall Space Flight Center  
Marshall Space Flight Center, Alabama*

1. REPORT NO. TM X-64534	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO.	
4. TITLE AND SUBTITLE Interpolation of Bode's Tables of the Solar Continuous Absorption Coefficient		5. REPORT DATE July 1, 1970	
		6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S) Edward M. Wadsworth		8. PERFORMING ORGANIZATION REPORT #	
9. PERFORMING ORGANIZATION NAME AND ADDRESS George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812		10. WORK UNIT NO.	
		11. CONTRACT OR GRANT NO.	
12. SPONSORING AGENCY NAME AND ADDRESS		13. TYPE OF REPORT & PERIOD COVERED Technical Memorandum	
		14. SPONSORING AGENCY CODE	
15. SUPPLEMENTARY NOTES Prepared by Space Sciences Laboratory, Science and Engineering Directorate			
16. ABSTRACT <p>Knowledge of the total continuous absorption coefficient for a wide range of wavelengths is vital to many areas of solar physics, such as the construction of model atmospheres and line profile calculations. Recently, Gerhard Bode compiled a set of tables for the continuous absorption coefficient for the sun covering a wide range of wavelengths, electron pressures, and temperatures. To obtain the absorption coefficient as a function of electron pressure and temperature at an untabulated wavelength, one can employ standard interpolation formulas using the several wavelengths listed, which are between major absorption edges and span the desired wavelength. At a given wavelength the absorption coefficients at particular temperatures and pressures not given in the table can be obtained by a double linear interpolation scheme. This paper describes a computer subprogram which has been developed to calculate the solar continuous absorption coefficient for any given model atmosphere.</p>			
17. KEY WORDS		18. DISTRIBUTION STATEMENT  For Public Release  <i>Mona J. Hagyard</i>	
19. SECURITY CLASSIF. (of this report) Unclassified	20. SECURITY CLASSIF. (of this page) Unclassified	21. NO. OF PAGES 16	22. PRICE \$3.00

## ACKNOWLEDGMENT

The assistance of Dr. Mona Hagyard of the Space Sciences Laboratory is gratefully acknowledged.

# TABLE OF CONTENTS

	Page
SUMMARY .....	1
INTRODUCTION .....	1
THE TECHNIQUE OF DOUBLE INTERPOLATION .....	2
CONCLUSIONS .....	6
APPENDIX A: COMPUTER FLOW CHART .....	8
APPENDIX B: COMPUTER SUBPROGRAM .....	9
REFERENCES .....	10

## LIST OF TABLES

Table	Title	Page
1.	Values of Log (Pe/K) .....	2
2A.	Constant Log (Pe) Values; Log (Pe) = -2.5 .....	3
2B.	Constant Log (Pe) Values; Log (Pe) = -2.0 .....	3
3A.	Constant $\theta$ Values; $\theta = 1.25$ .....	4
3B.	Constant $\theta$ Values; $\theta = 1.20$ .....	4

## INTERPOLATION OF BODE'S TABLES OF THE SOLAR CONTINUOUS ABSORPTION COEFFICIENT

### SUMMARY

Knowledge of the total continuous absorption coefficient for a wide range of wavelengths is vital to many areas of solar physics, such as the construction of model atmospheres and line profile calculations. Recently, Gerhard Bode [1] compiled a set of tables for the continuous absorption coefficient for the sun covering a wide range of wavelengths, electron pressures, and temperatures. To obtain the absorption coefficient as a function of electron pressure and temperature at an untabulated wavelength, one can employ standard interpolation formulas using the several wavelengths listed, which are between major absorption edges and span the desired wavelength. At a given wavelength the absorption coefficients at particular temperatures and pressures not given in the table can be obtained by a double linear interpolation scheme. This paper describes a computer subprogram which has been developed to calculate the solar continuous absorption coefficient for any given model atmosphere.

### INTRODUCTION

The subprogram used to interpolate the Bode data employs a method of two-way differences. This method is described in detail by Scarborough [2].

It is hoped that an example problem of the technique of two-way differences will clarify the procedure used to interpolate the Bode tables by computer. A flow chart (Appendix A) is also used to indicate the processes undertaken by the computer; the subroutine is listed in Appendix B.

## THE TECHNIQUE OF DOUBLE INTERPOLATION

The example problem uses a table of values of  $\log$  (electron pressure/absorption coefficient) at 5250.20 Å vs  $\log$  (electron pressure) and  $\theta$ , where  $\theta$  is 5040/absolute temperature.

It should be noted that there is no Bode table for 5250.20 Å; rather Table 1 was compiled using a simple straight-line interpolation of a Bode table at 4500.00 Å and one at 5698.50 Å.

TABLE 1. VALUES OF  $\log$  (Pe/K)

$\theta$	$\log$ (Pe)					
	-2.5	-2.0	-1.5	-1.0	-0.5	0.0
1.30	24.376	24.569	24.658	24.693	24.713	24.758
1.25	24.412	24.625	24.727	24.767	24.784	24.806
1.20	24.443	24.681	24.797	24.884	24.861	24.872
1.15	24.465	24.729	24.865	24.922	24.942	24.950
1.10	24.452	24.767	24.927	24.999	25.024	24.033
1.05	24.313	24.768	24.985	25.072	25.105	25.117
1.00	23.914	24.627	25.004	25.138	25.183	25.202
0.95	23.298	24.200	24.879	25.174	25.255	25.281

Suppose that a value of  $\log$  (Pe/K) is needed for particular values of  $\theta$  and  $\log$  (Pe) not given in Table 1. The method of two-way differences would then be used as follows:

**Problem:**  $\log$  (Pe/K) needs to be calculated at a  $\theta$  value of 1.22 and a  $\log$  (Pe) value of -2.2 at 5250.20 Å.

**Solution:** Tables 2A and 2B show forward differences for constant  $\log$  (Pe) values, and Tables 3A and 3B show differences for constant  $\theta$  values (hence, two-way differences). A general formula for double interpolation uses these differences in providing the desired value of  $\log$  (Pe/K). Note that  $\log$  (Pe/K) = 24.412 at  $\theta = 1.25$  and  $\log$  (Pe) = -2.5 is used as a "starting point" for taking differences. The starting point is that value of

$\log (Pe/K)$  in Table 1 for which the corresponding values of  $\log (Pe)$  and  $\theta$  are closest to and above those which are being interpolated.

TABLE 2A. CONSTANT LOG (Pe) VALUES; LOG (Pe) = -2.5

	$K(\theta, -2.5)$	$\Delta^{1+0}_{\kappa_{\theta 0}}$	$\Delta^{2+0}_{\kappa_{\theta 0}}$
$\theta_0 = 1.25$	24.412		
$\theta_1 = 1.20$	24.443	0.031	-0.009
$\theta_2 = 1.15$	24.465	0.022	

TABLE 2B. CONSTANT LOG (Pe) VALUES; LOG (Pe) = -2.0

	$K(\theta, -2.0)$	$\Delta^{1+0}_{\kappa_{\theta 1}}$	$\Delta^{2+0}_{\kappa_{\theta 1}}$
$\theta_0 = 1.25$	24.625		
$\theta_1 = 1.20$	24.699	0.074	-0.044
$\theta_2 = 1.15$	24.729	0.030	

a.  $K_{00}$  is the starting point for taking differences;

$$K(\theta, \log Pe) = \log (Pe/K)$$

$$\left. \begin{array}{l} \Delta^{1+0}_{\kappa_{\theta Pe}} \\ \Delta^{0+1}_{\kappa_{\theta Pe}} \end{array} \right\} = \text{First-order difference,}$$

$$\left. \begin{array}{l} \Delta^{2+0}_{\kappa_{\theta Pe}} \\ \Delta^{0+2}_{\kappa_{\theta Pe}} \end{array} \right\} = \text{Second-order difference.}$$

Also,

$$\Delta^{1+1}_{\kappa_{\theta Pe}} = \Delta^{1+0}_{\kappa_{\theta 1}} - \Delta^{1+0}_{\kappa_{\theta 0}} = \Delta^{0+1}_{\kappa_{1Pe}} - \Delta^{0+1}_{\kappa_{0Pe}}$$

TABLE 3A. CONSTANT  $\theta$  VALUES;  $\theta = 1.25$ 

	$K(1.25, \text{Log Pe})$	$\Delta^{0+1}_{\kappa_{1\text{Pe}}}^a$	$\Delta^{0+2}_{\kappa_{1\text{Pe}}}^a$
$\text{Log Pe}_0 = -2.5$	24.412	0.213 0.102	-0.111
$\text{Log Pe}_1 = -2.0$	24.625		
$\text{Log Pe}_2 = -1.5$	24.727		

TABLE 3B. CONSTANT  $\theta$  VALUES;  $\theta = 1.20$ 

	$K(1.20, \text{Pe})$	$\Delta^{0+1}_{\kappa_{1\text{Pe}}}^a$	$\Delta^{0+2}_{\kappa_{1\text{Pe}}}^a$
$\text{Log Pe}_0 = -2.5$	24.443	0.256 0.098	-0.158
$\text{Log Pe}_1 = -2.0$	24.699		
$\text{Log Pe}_2 = -1.5$	24.797		

a.  $K_{00}$  is the starting point for taking differences;

$$K(\theta, \text{Log Pe}) = \text{Log} (\text{Pe}/K)$$

$$\left. \begin{array}{l} \Delta^{1+0}_{\kappa_{\theta\text{Pe}}} \\ \Delta^{0+1}_{\kappa_{\theta\text{Pe}}} \end{array} \right\} = \text{First-order difference,}$$

$$\left. \begin{array}{l} \Delta^{2+0}_{\kappa_{\theta\text{Pe}}} \\ \Delta^{0+2}_{\kappa_{\theta\text{Pe}}} \end{array} \right\} = \text{Second-order difference.}$$

Also,

$$\Delta^{1+1}_{\kappa_{\theta\text{Pe}}} = \Delta^{1+0}_{\kappa_{\theta 1}} - \Delta^{1+0}_{\kappa_{\theta 0}} = \Delta^{0+1}_{\kappa_{1\text{Pe}}} - \Delta^{0+1}_{\kappa_{0\text{Pe}}}$$

The general formula for double interpolation using two-way differences is:



$$K = K_{00} + u \cdot \Delta^{1+0}_{\kappa_{00}} + v \cdot \Delta^{0+1}_{\kappa_{00}} + \frac{1}{2!} \left[ u(u-1) \cdot \Delta^{2+0}_{\kappa_{00}} + 2u \cdot v \cdot \Delta^{1+1}_{\kappa_{00}} + v(v-1) \cdot \Delta^{0+2}_{\kappa_{00}} \right]$$

where

$$u = \frac{\theta - \theta_0}{\theta_1 - \theta_0}$$

and

$$v = \frac{\text{Log}(\text{Pe}) - \text{Log}(\text{Pe})_0}{\text{Log}(\text{Pe})_1 - \text{Log}(\text{Pe})_0}$$

From Table 1,

$$K_{00} = 24.412$$

$$\Delta^{1+0}_{\kappa_{00}} = 0.031$$

$$\Delta^{0+1}_{\kappa_{00}} = 0.213$$

$$\Delta^{2+0}_{\kappa_{00}} = -0.009$$

$$\Delta^{0+2}_{\kappa_{00}} = -0.111$$

Also,

$$\Delta^{1+1}_{\kappa_{00}} = \Delta^{1+0}_{\kappa_{\theta 1}} - \Delta^{1+0}_{\kappa_{\theta 0}} = 0.043$$

For u and v :

$$u = \frac{1.22 - 1.25}{-0.05} = 0.6$$

$$v = \frac{-2.3 - (-2.5)}{0.5} = 0.4$$

Then,

$$\begin{aligned} \text{Log (Pe/K)} &= 24.412 + (0.6)(0.031) + (0.4)(0.213) \\ &+ \frac{1}{2} \left[ (0.6)(-0.4)(-0.009) + 2(0.6)(0.4)(0.043) \right. \\ &\quad \left. + (0.4)(-0.06)(-0.111) \right] = 24.541 \end{aligned}$$

Before the computer takes differences from Table 1, it first finds a suitable starting point. In the preceding example the computer would go to 24.412 to start taking differences. If a  $\theta$  value of 1.12 and a  $\log(\text{Pe})$  value of -1.1 were read into the computer, the calculations would begin at 24.865 as a starting point. The computer scans those values of  $\theta$  and  $\log(\text{Pe})$  in Table 1 until it finds the ones that are closest to but higher in the table than the  $\theta$  and  $\log(\text{Pe})$  values read in. Then the  $\log(\text{Pe/K})$  value corresponding to these values of  $\theta$  and  $\log(\text{Pe})$  is used as a starting point for taking differences. In this way the best possible interpolated value of  $\log(\text{Pe/K})$  is obtained.

## CONCLUSIONS


Some restrictions on using the subroutine should be mentioned. In Table 1, the values of  $\theta$  must increase by equal amounts (-0.05 in this case); similarly, the values of  $\log(\text{Pe})$  must increase by equal steps.

For the subroutine to function, it must be able to take first- and second-order differences from Table 1. As long as the value of  $\theta$  in the

interpolation is not equal to or smaller than 1.00 and the value of  $\log(Pe)$  is not equal to or greater than  $-0.05$ , the calculations in the subroutine will be carried out. If this restriction is not observed, the table must be made larger, or the interpolation subroutine must be made to take only first-order differences.

# APPENDIX A

## COMPUTER FLOW CHART



# APPENDIX B

## COMPUTER SUBPROGRAM

```

&FOR,IS OPAC
SUBROUTINE OPAC(X,THETA,PE,WV,AKCG)
DIMENSION XKAPP(9,7),XLOG(7),THET(9)
COMMON XKAPP
THET(1)=1.35
90 DO 100 I=2,9
100 THET(I)=THET(I-1)-.05
CONTINUE
XLOG(1)=-3.0
120 DO 130 K=2,7
130 XLOG(K)=XLOG(K-1)+.5
CONTINUE
160 XTHET=0.0
170 YTHET=0.0
180 I=1
190 I=I+1
200 XTHET=THET(I)
YTHET=THETA
220 IF (.05-(XTHET-YTHET)) 190,230,230
230 U=0.0
240 U=(XTHET-YTHET)/.05
250 K=1
260 K=K+1
270 ZLOG=0.0
280 ZLOG=XLOG(K)
290 WLOG=0.0
WLOG=.434294*ALOG(PE)
310 IF (.5+(ZLOG-WLOG)) 260,320,320
320 V=0.0
330 V=(WLOG-ZLOG)/.5
340 FIRT=0.0
350 FIRT=XKAPP(I+1,K)-XKAPP(I,K)
360 SECT=0.0
370 SECT=XKAPP(I+2,K)-XKAPP(I+1,K)
380 FIRL=0.0
390 FIRL=XKAPP(I,K+1)-XKAPP(I,K)
400 SECL=0.0
410 SECL=XKAPP(I,K+2)-XKAPP(I,K+1)
420 SECTO=0.0
430 SECTO=SECT-FIRT
440 SECLO=0.0
450 SECLO=SECL-FIRL
460 DA=0.0
470 DA=XKAPP(I+1,K+1)-XKAPP(I,K+1)
480 DX=0.0
490 DX=DA-FIRT
500 XCAP=0.0
510 XCAP=XKAPP(I,K)+U*FIRT+V*FIRL+(SECTO*(U-1.)*U+2.*U*V*DX+SECLO*(V-1.)*V)/2.
XAKCG=0.0
XAKCG=23.6203-(XCAP-WLOG)
Y=0.0
Y=XAKCG*2.30258
AKCG=0.0
AKCG=EXP(Y)
RETURN
END

```

## REFERENCES

1. Bode, Gerhard: Die kontinuierliche Absorption von Sternatmosphären in Abhängigkeit von Druck, Temperatur und Elementhäufigkeiten. Institut für Theoretische Physik und Sternwarte der Universität Kiel, Germany, 1965.
2. Scarborough, James B.: Numerical Mathematical Analysis. The Johns Hopkins Press, Baltimore, Md., 1950.


## APPROVAL


INTERPOLATION OF BODE'S TABLES OF THE  
SOLAR CONTINUOUS ABSORPTION COEFFICIENT

By Edward M. Wadsworth

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

This document has also been reviewed and approved for technical accuracy.

  
WILLIAM C. SNODDY  
Chief, Space Thermophysics Division

  
GERHARD B. HELLER  
Director, Space Sciences Laboratory

# DISTRIBUTION

TM X-64534

## INTERNAL

### S&E-SSL-DIR

Mr. Gerhard B. Heller  
Mr. Ray V. Hembree

### S&E-SSL-C

Reserve (10)

### S&E-SSL-N

Dr. Rudolf Decher  
Mr. Henry Stern

### S&E-SSL-P

Dr. Robert Naumann

### S&E-SSL-S

Dr. Werner Sieber

### S&E-SSL-T

Mr. William Snoddy

### S&E-SSL-TE

Mr. Edgar Miller

### S&E-SSL-TR

Mr. Gary Arnett

### S&E-SSL-TT

Mr. Billy P. Jones  
Dr. Mona Hagyard (5)  
Dr. Allen Gary  
Mr. Daniel Gates  
Mr. Ted Calvert  
Mr. Creighton Miller  
Mr. Paul Craven  
Mr. James Watkins  
Mr. Edward Wadsworth (10)

### A&TS-MS-IP (2)

### A&TS-MA-PT

Mr. Mark Russell

### A&TS-MS-IL (8)

### A&TS-TU (6)

### A&TS-MS-H

### PM-PR-M

### A&TS-PAT

L. D. Wofford, Jr.

### DEP-T

### DIR

## EXTERNAL

### Scientific and Technical Information

Facility (25)  
P. O. Box 33  
College Park, Maryland 20740  
Attn: NASA Representative (S-AK/RKT)